

吊篮用钢丝绳 技术参数 Technical parameter

4×25Fi+FC 、 4×31SW+FC

公称直径 Nominal Diameter	公称抗拉强度 Nominal Tensile Strength, MPa						参考重量 Approximate Weight
	1870	1960	2060	2160	2260	2360	
mm	最小破断拉力 Min,Breaking Load, kN						kg/100m
8.0	41.0	43.0	45.2	47.4	49.6	51.8	24.3
8.3	44.2	46.3	48.7	51.0	53.4	55.8	26.4
8.6	47.1	49.3	51.9	54.4	56.9	59.4	28.3
9.0	51.3	53.8	56.5	59.3	62.0	64.8	32.0
9.5	57.3	60.1	63.1	66.2	69.3	72.3	35.5
10.0	63.6	66.7	70.1	73.5	76.9	80.3	39.0

6×19W+IWS 、 6×19S+IWR

公称直径 Nominal Diameter	公称抗拉强度 Nominal Tensile Strength, MPa						参考重量 Approximate Weight
	1870	1960	2060	2160	2260	2360	
mm	最小破断拉力 Min,Breaking Load, kN						kg/100m
8.0	49.4	51.8	54.4	57.1	59.7	62.3	27.0
8.3	53.0	55.5	58.3	61.2	64.0	66.8	29.6
8.6	56.7	59.5	62.5	65.5	68.6	71.6	32.5
9.0	64.2	67.3	70.7	74.1	77.6	81.0	34.1
9.5	69.3	72.6	76.3	80.0	83.8	87.5	37.5
10.0	78.9	82.7	86.9	91.1	95.4	99.6	41.6

注：根据顾客需要，还可提供其他规格、抗拉强度的产品 NOTE:Providing engineer design sa per customer's request