

特种门机及健身器械用钢丝绳 技术参数 Technical parameter

结构	公称直径 Nominal Diameter mm	允许偏差 Tolerance mm	绳最小破 断拉力 Min B/L kN	锌层重量 g/m ²	切断处直径 允许增大值 mm	参考重量 kg/100m
6×19-WSC	3.18	+0.50	9.0	≥10	0.30	4.31
	4.00	+0.50	12.45	≥10	0.45	6.70
6×19-SPC	3.18	+0.50	8.0	≥10	0.30	4.30

结构	公称直径 Nominal Diameter mm	允许偏差 Tolerance mm	绳最小破断拉力 Min B/L kN	切割后直径 最大值 mm	参考重量 kg/100m
6×7-WSC	1.2	+10 0	1.2	1.60	0.65
	1.6		2.2	2.10	1.2
	2.4	+8 0	4.1	2.95	2.4
6×19-WSC	2.4	+8 0	4.5	2.95	2.6
	3.0		7.3	3.65	4.2
	3.2		8.9	3.95	4.3
	3.6		9.1	4.35	6.0
	4.0		12.5	4.85	6.7
	4.2	+7 0	13.7	5.05	8.2
	4.8		18.6	5.75	9.7
	5.6		24.9	6.55	12.8
	6.4		31.2	7.40	16.4
	7.2		35.6	8.30	20.8
	8.0		43.6	9.15	25.8
	9.5		64.1	10.85	36.2